SR3 FÉLVEZETŐ RELÉK 15-75 A ST

SR3 sorozat

SR3-1230
SSR 3f 30A IN:4-32VDC/OUT24-240VAC, v 0




- 3f relé hűtőborda nélkül, kerámiabetéttel a maximális hőátadás érdekében
- Kompakt méretek - a modul magassága mindössze 32,2 mm
- A kapcsolás LED-es kijelzése
- Nulla vagy pillanatnyi kapcsolás


TERMÉKLEÍRÁS

MŰSZAKI ADATOK




2421_Peak current (A)	400
Activation	0 V
Control voltage	4-30 VDC
Csúcsfeszültség	600 V
Fázisok száma	3
I2t-érték	1000 A²s
Jóváhagyások	CE, cRUus
Kikapcsolási feszültség	1 V
Max. tárolási hőmérséklet	100 °C
Max. terhelőáram, AC	30 A
Max. üzemi hőmérséklet	80 °C
Min. tárolási hőmérséklet	-30 °C
Min. üzemi hőmérséklet	-30 °C
Output voltage (String)	24-240 VAC
Szélesség	110 mm
Szigetelés ellenállása	100 MΩ
Tömeg	275 g




• Panel cut-out




※Detachable heatsink type screw tightening torque
for mounting: 2.5N·m to 3N·m

3-phase (2-pole)	3-phase (3-pole) delta connection (△-connection)	3-phase (3-pole) star connection (Y-connection)
		




※For DC signal input models, 8 and 10 terminals are connected inside.
※For AC signal input models, 8 and 10 terminals are insulated inside.



• Panel cut-out



※Detachable heatsink type screw tightening torque
for mounting: 2.5N·m to 3N·m

3-phase (2-pole)	3-phase (3-pole) delta connection (△-connection)	3-phase (3-pole) star connection (Y-connection)
		

※For DC signal input models, 8 and 10 terminals are connected inside.
※For AC signal input models, 8 and 10 terminals are insulated inside.