



FŰTÉS 10-30W - HGK 047

04716.0-00

HGK 047 30W Heater with cable, 12-36V ac/dc



- Dinamikus fűtés (PTC elem)
- Kompakt
- Energiatakarékos
- Gyors csatlakozó a DIN sínhez



TERMÉKLEÍRÁS

The heat source in the element consists of a PTC element – a semi-conductor that adapts its output to the ambient temperature.

The PTC element has a high starting current and provides full output almost immediately. The current then falls quickly and the element is thereafter self-regulating, meaning that the warmer the surroundings, the less output produced by the element.

Thanks to the chimney effect, meaning that the colder air is drawn into the element's bottom and discharged at the top, good self-circulation is achieved for the heated air.

The heating element is best installed in smaller cabinets so as avoid condensation or that the temperature falls beneath the minimum level.

MŰSZAKI ADATOK

Heat Output	30 W
Heater	Eloxált alumínium
Humidity Storage	<90% RH
IP-osztály	IP44
Jóváhagyások	CE, EAC, Gost R, RoHS
Kábelhossz	300 mm
Magasság	100 mm
Max. feszültség	36 V ac/dc
Max. indítóáram	4 A
Mélység	50 mm

Nominal voltage	12-36 V AC/DC
Operating Humidity	< 90% RH
Operational Temperature	-45°C ... +70°C
Szélesség	25 mm
Tárolási hőmérséklet	-45°C ... +70°C
Tömeg	0,2 kg
Védelmi osztály	I (földelt)
Voltage min	12 V ac/dc

