



FŰTÉS 15-150W - HG 140

14013.0-00

HG 140 60W Heater, 12-36V ac/dc



- Dinamikus fűtés (PTC elem)
- Kompakt
- Energiatakarékos
- Gyors csatlakozó és gyors telepítés



TERMÉKLEÍRÁS

The heat source in the element consists of a PTC element – a semi-conductor that adapts its output to the ambient temperature.

The PTC element has a high starting current and provides full output almost immediately. The current then falls quickly and the element is thereafter self-regulating, meaning that the warmer the surroundings, the less output produced by the element.

Thanks to the chimney effect, meaning that the cold air is drawn into the element's bottom and blows out at the top, good self-circulation is achieved for the heated air.

The addition of Pressure Clamp terminals saves time and simplifies the installation.

MŰSZAKI ADATOK

Heat Output	60 W
Heater	Eloxált alumínium
Humidity Storage	<90% RH
IP-osztály	IP20
Jóváhagyások	CE, EAC, Gost R, RoHS, VDE
Magasság	179 mm
Max. feszültség	36 V ac/dc
Max. indítóáram	10 A
Mélység	60 mm
Nominal voltage	24 V AC/DC

Operating Humidity	< 90% RH
Operational Temperature	-45°C ... +70°C
Szélesség	70 mm
Tárolási hőmérséklet	-45°C ... +70°C
Tömeg	0,4 kg
Védelmi osztály	I (földelt)
Voltage min	12 V ac/dc

