



FŰTÉS 50-150W - CS 060

06020.0-00

CS 060 150W Touch-safe heater, 120-240V ac/dc



- Nem igényel földelést
- Kis méret
- Alacsony felületi hőmérséklet
- DIN sínkapocs



TERMÉKLEÍRÁS

This series of powerful and compact heaters has several benefits, both during installation and in operation. The heater is available in the following outputs: 50, 100 and 150 W.

It is easily installed thanks to the mounting clips for DIN rails that are fitted on the back of the heater.

Because the heater is dual isolated with a plastic casing, the side surfaces' temperature never exceeds 80 °C. The heater can thus be mounted relatively close to other components in the same installation, and there is no risk for fire damage. The dual isolation also means that the heater does not need to be earthed.

The heat source consist of a PTC element, which provides a long and reliable lifetime even if the heater is in constant operation. This type of heater is also available with an attached thermostat with static set values, which further simplifies installation and operation. For this model, see CSF060.

MŰSZAKI ADATOK

Heat Output	150 W
Heater	Műanyag
Humidity Storage	<90% RH
IP-osztály	IP20
Jóváhagyások	CE, EAC, Gost R, RoHS, UL E150057, VDE
Magasság	150 mm
Max. feszültség	265 V ac/dc
Max. indítóáram	8 A
Mélység	90 mm

Nominal voltage	120-240 V AC/DC
Operating Humidity	< 90% RH
Operational Temperature	-45°C ... +70°C
Pre fuse (slow)	10 A
Szélesség	60 mm
Tárolási hőmérséklet	-45°C ... +70°C
Temperature 50 Mm Above The Heater	145 °C (293 °F)
Tömeg	0,5 kg
Védelmi osztály	II (kettős szigetelésű)
Voltage min	110 V ac/dc

