



FŰTÉS 50-150W - CSF 060

06022.0-00

CSF 060 150W Touch-safe heater inc stat, 120-240V
ac, 25°C

- Nem igényel földelést
- Termosztáttal szerelve
- Alacsony felületi hőmérséklet
- DIN sínkapocs



TERMÉKLEÍRÁS

This series of powerful and compact heaters has several benefits, both during installation and in operation. The heaters are available in the following outputs: 50, 100 and 150 W.

They are easily installed thanks to the mounting clips for DIN rails that are fitted on the back of the heaters.

This model is supplied with a plug in tamper-proof preset thermostat, so does not require any additional components or wiring, only two cables for power need to be connected and the heater is ready for use.

Because the heater is dual isolated with a plastic casing, the side surfaces' temperature never exceeds 80 °C. The heater can thus be mounted relatively close to other components in the same installation, and there is no risk for fire damage.

The dual isolation also means that the heater does not need to be earthed. The heat source consist of a PTC element, which provides a long and reliable lifetime even if the heater is in constant operation. This type of heater is also available without a thermostat. For this model, see CS060.

MŰSZAKI ADATOK

Heat Output	150 W
Heater	Műanyag
Humidity Storage	<90% RH
IP-osztály	IP20
Jóváhagyások	CE, EAC, Gost R, RoHS, UL E150057, VDE
Magasság	150 mm
Max. feszültség	265 V ac
Max. indítóáram	8 A

Mélység	90 mm
Nominal voltage	120-240 V AC/DC
Operating Humidity	< 90% RH
Operational Temperature	-45°C ... +70°C
Pre fuse (slow)	10 A
Szélesség	60 mm
Szín	Fekete
Tárolási hőmérséklet	-45°C ... +70°C
Temperature 50 Mm Above The Heater	+145 °C (+293 °F)
Temperature For Closing	15 °C
Temperature For Mining	25 °C
Tömeg	0,5 kg
Védelmi osztály	II (kettős szigetelésű)
Voltage min	110 V ac

