



Kalorimetrikus

302-es alaplap, 2 extra hely, G1/8" + 4 mm

-
- A black and silver industrial solenoid valve. The main body is black with a silver-colored base. It has two ports at the bottom with red-handled actuators. The top has a black solenoid coil assembly. Text on the side of the black body includes "2001110-01", "2W-PC-10", "P-10/10°C", and "10/10/10/10". There are also some small, less legible markings.

MŰSZAKI ADATOK

Test anyaga	Aluminium
Type of valve	Electrically controlled

Specifikation av vilken omgivningstemperatur ventilerna klarar, vilket är beroende av monterings sätt			
Effekt spole	Version av elektrisk anslutning		
0,55 kW	Standard	-10 °C till +50 °C	-10 °C till +50 °C
0,55 kW	Lyfödd + transistorslucht	-10 °C till +50 °C	-10 °C till +50 °C
1,05 kW	Standard	-25 °C till +40 °C	-25 °C till +40 °C
1,15 kW	Lyfödd + transistorslucht	-25 °C till +40 °C	-25 °C till +40 °C
2,20 kW	Standard	-10 °C till +40 °C	-10 °C till +40 °C
1,15 kW	Lyfödd + transistorslucht	-10 °C till +40 °C	-10 °C till +40 °C

