

**TÁPEGYSÉG 1 FÁZIS,  $\pm 12$  VDC /5 VDC  
MINILINE SZÉRIA** $\pm 12$ -15 V DC, 2,5 A

ML30.106

PSU 100-240V ac I/P 30V dc 2.5A 36W O/P

- Kimeneti áramerősség 4.2 A vagy 5 A
- Magas hatásfok
- Helytakarékos
- Képes kezelni a magas indítási illetve túlterhelési áramot is
- Rugós csatlakozás

**TERMÉKLEÍRÁS****MŰSZAKI ADATOK**

|                                               |                                  |
|-----------------------------------------------|----------------------------------|
| Active Transient                              | Igen                             |
| Clamp type                                    | Spring-clamp                     |
| Efficiency At 230 V AC, full load. Typical    | 86 %                             |
| Fázisok száma                                 | 1                                |
| Hold-up time at 120 V AC, full load. Typical. | 18 ms                            |
| Hold-up time at 230 V AC, full load. Typical. | 180 ms                           |
| Input voltage AC                              | 100-240 V                        |
| Input voltage ac max                          | 264 V AC                         |
| Input voltage ac min                          | 85 V AC                          |
| Input voltage DC                              | 110-300 V                        |
| Input voltage dc max                          | 375 V DC                         |
| Input voltage dc min                          | 85 V DC                          |
| Input voltage range                           | Wide-range                       |
| Inrush current at 120 V ac typical            | 17 A                             |
| Inrush current at 230 V ac typical            | 35 A                             |
| IP-osztály                                    | IP20                             |
| Jóváhagyások                                  | CB, CE, CSA, GL, NEC Class 2, UL |
| Magasság                                      | 75 mm                            |
| Mélység                                       | 91 mm                            |

|                                                       |             |
|-------------------------------------------------------|-------------|
| <b>MTBF (IEC 61709) 230 V AC, Maximum Load, 40 °C</b> | 600000 h    |
| <b>Output Current</b>                                 | 2,5 A       |
| <b>Output voltage</b>                                 | 12 V DC     |
| <b>Output voltage max</b>                             | 15 V DC     |
| <b>Output voltage min</b>                             | 12 V DC     |
| <b>Power Consumption At 120 V AC</b>                  | 0,65 A      |
| <b>Power Consumption At 230 V AC</b>                  | 0,4 A       |
| <b>Power Factor at 120 V AC, full load. Typical</b>   | 0,53        |
| <b>Power Factor at 230 V AC, full load. Typical</b>   | 0,53        |
| <b>Power Reduction Of 60 To 70 ° C</b>                | 1 W/°C      |
| <b>Ripple. max</b>                                    | 50 mV pp    |
| <b>Series</b>                                         | Miniline    |
| <b>Supply Frequency</b>                               | 50-60 ±6 %  |
| <b>Szélesség</b>                                      | 45 mm       |
| <b>Teljesítmény</b>                                   | 30 W        |
| <b>Temperature Range Without Derating From</b>        | -10 °C      |
| <b>Temperature Range Without Derating To</b>          | 60 °C       |
| <b>Type Power Supply</b>                              | AC-DC       |
| <b>Tömeg</b>                                          | 0,24 kg     |
| <b>Védőanyag</b>                                      | ABS műanyag |

