

**TÁPEGYSÉG 1 FÁZIS, 48 VDC MINILINE SZÉRIA**

48-56 V DC, 1,05 A és 2,1 A

ML50.105

PSU 100-240V ac I/P 48V dc 1A 50W O/P

- Kimeneti áramerősség 1 A vagy 2.1 A
- Magas hatásfok
- Helytakarékos
- Képes kezelni a magas indítási illetve túlterhelési áramot is
- Rugós csatlakozás

**TERMÉKLEÍRÁS****MŰSZAKI ADATOK**

|                                               |                              |
|-----------------------------------------------|------------------------------|
| Clamp type                                    | Spring-clamp                 |
| Efficiency At 230 V AC, full load. Typical    | 90 %                         |
| Fázisok száma                                 | 1                            |
| Hold-up time at 120 V AC, full load. Typical. | 17 ms                        |
| Hold-up time at 230 V AC, full load. Typical. | 170 ms                       |
| Input voltage AC                              | 100-240 V                    |
| Input voltage ac max                          | 264 V AC                     |
| Input voltage ac min                          | 85 V AC                      |
| Input voltage DC                              | 110-300 V                    |
| Input voltage dc max                          | 375 V DC                     |
| Input voltage dc min                          | 85 V DC                      |
| Input voltage range                           | Wide-range                   |
| Inrush current at 120 V ac typical            | 17 A                         |
| Inrush current at 230 V ac typical            | 35 A                         |
| IP-osztály                                    | IP20                         |
| Jóváhagyások                                  | CB, CE, CSA, NEC Class 2, UL |

|                                                 |             |
|-------------------------------------------------|-------------|
| Magasság                                        | 75 mm       |
| Mélység                                         | 91 mm       |
| MTBF (IEC 61709) 230 V AC, Maximum Load, 40 ° C | 600000 h    |
| Output Current                                  | 1,05 A      |
| Output voltage                                  | 48 V DC     |
| Output voltage max                              | 56 V DC     |
| Output voltage min                              | 48 V DC     |
| Power Consumption At 120 V AC                   | 1 A         |
| Power Consumption At 230 V AC                   | 0,6 A       |
| Power Factor at 120 V AC, full load. Typical    | 0,52        |
| Power Factor at 230 V AC, full load. Typical    | 0,52        |
| Power Reduction Of 60 To 70 ° C                 | 1,3 W/°C    |
| Ripple. max                                     | 50 mV pp    |
| Series                                          | Miniline    |
| Supply Frequency                                | 50-60 ±6 %  |
| Szélesség                                       | 45 mm       |
| Teljesítmény                                    | 50 W        |
| Temperature Range Without Derating From         | -10 °C      |
| Temperature Range Without Derating To           | 60 °C       |
| Type Power Supply                               | AC-DC       |
| Tömeg                                           | 0,24 kg     |
| Védőanyag                                       | ABS műanyag |

