



## 24 V DC-UPS MODUL KÜLÖNÁLLÓ MODULKÉNT, AKKUMLÁTOR NÉLKÜL 3.9-40 AH

Külső akkumulátor 3,9-150 Ah

UB20.241

DC UPS 24V dc I/P 24V dc 20A O/P 3.9-150Ah

- Terhelési áramerősség 20 A
- Egyes akkumulátorok külön vezérlése
- Választható kimeneti feszültség az akkumulátor üzemmódban
- Hőmérséklet kompenzált töltés
- Relé visszajelző a tápegység állapotáról



# PULS

### TERMÉKLEÍRÁS

## MŰSZAKI ADATOK

Charging The Battery Type	3 A
Efficiency	99 %
Élettartam	122 000 h @ 20 A, 40 °C
Input Current During Charging Of Aggregates	3,4 A
Input voltage for battery connection	22,8 V DC
Input Voltage From battery	24 V DC
Input Voltage From The Unit	24 V DC
IP-osztály	IP20
Jóváhagyások	ABS, CB, CE, CSA, CSA US, EX, GL, IECEx, UL
Magasság	124 mm
Mélység	117 mm
MTBF (IEC 61709)	649 000 h @ 20 A, 40 °C
Output current at 24 V dc	20 A
Output Current During Normal Operation Via The Unit Max	25 A
Output current for battery operation max	20 A (30 A @ 4 s)

<b>Output Voltage at Battery</b>	22,5
<b>Output Voltage Normal Operation</b>	24 V DC
<b>Permitted Battery Sizes</b>	3,9-150 Ah
<b>Power Reduction Of 60 To 70 ° C</b>	12 W/°C
<b>Ripple. max</b>	120 mV pp
<b>Szélesség</b>	49 mm
<b>Temperature Range Without Derating From</b>	-40 °C
<b>Temperature Range Without Derating To</b>	60 °C
<b>Tömeg</b>	0,7 kg
<b>Védőanyag</b>	Alumínium
<b>Voltage Level Of The Connection Of The Battery</b>	24 V DC



