

**BUFFER MODUL, 24 V DC  
SZUPERKONDENZÁTORRAL, EDLC**

UC10.242

DC UPS 24V dc I/P 24V dc 15A O/P 12kW

- Terhelési áramerősség 15 A
- 6 kW - 12 kW
- Hosszú buffer idő
- Karbantartás
- Hosszú élettartam

**TERMÉKLEÍRÁS****MŰSZAKI ADATOK**

|                                                         |                                    |
|---------------------------------------------------------|------------------------------------|
| Charging The Battery Type                               | 1,1 A                              |
| Efficiency                                              | 97,8 %                             |
| Élettartam                                              | 96 000 h @ 15 A, 40 °C, 75%        |
| Input Current During Charging Of Aggregates             | 1,3 A                              |
| Input voltage for battery connection                    | 22,8 V DC                          |
| Input Voltage From The Unit                             | 24 V DC                            |
| IP-osztály                                              | IP20                               |
| Jóváhagyások                                            | CB, CE, CSA, CSA US, EX, IECEx, UL |
| Magasság                                                | 124 mm                             |
| Mélység                                                 | 117 mm                             |
| MTBF (IEC 61709)                                        | 850 000 h @ 15 A, 40 °C            |
| Output current at 24 V dc                               | 15 A                               |
| Output Current During Normal Operation Via The Unit Max | 15 A                               |
| Output Current In Buffer Mode Max                       | 15 A                               |
| Output Voltage At Buffering                             | 22,45 V DC                         |

|                                                  |               |
|--------------------------------------------------|---------------|
| Output Voltage Normal Operation                  | 24 V DC       |
| Ripple. max                                      | 30 mV pp      |
| Szélesség                                        | 198 mm        |
| Temperature Range Without Derating From          | -40 °C        |
| Temperature Range Without Derating To            | 60 °C         |
| Type Power Supply                                | Buffer Module |
| Tömeg                                            | 1,72 kg       |
| Védőanyag                                        | Alumínium     |
| Voltage Level Of Activation Of The Buffer Module | 22,45 V DC    |

