



1 FÁZISÚ AS-INTERFACE DIN SÍNRE, SILVERLINE SZÉRIA

SLA4.100

ASI PSU 100-120/220-240V ac I/P 30.5V dc 4A O/P

- Kimeneti áramerősség 2.8, 4 és 8 A
- 115/230 V AC
- IR címzési mód
- Túlterhelés elleni védelem biztosítékkal (SLA8)
- Földhiba-figyelés relén keresztül (SLA4)



TERMÉKLEÍRÁS

MŰSZAKI ADATOK

Efficiency At 230 V AC, full load. Typical	88 %
Hold-up time at 120 V AC, full load. Typical.	30 ms
Hold-up time at 230 V AC, full load. Typical.	30 ms
Input voltage AC	100-120, 220-240 V
Input voltage ac max	264 V AC
Input voltage ac min	85 V AC
Input voltage range	Auto-select
Inrush current at 120 V ac typical	45 A
Inrush current at 230 V ac typical	50 A
IP-osztály	IP20
Jóváhagyások	CB, CE, CSA, UL
Magasság	124 mm
Mélység	102 mm
MTBF (IEC 61709) 230 V AC, Maximum Load, 40 ° C	1222000 h
Output Current	4 A

Output voltage	30,55 V DC
Output voltage max	30,5 V DC
Output voltage min	30,5 V DC
Power Consumption At 120 V AC	2,7 A
Power Consumption At 230 V AC	1,3 A
Power Factor at 120 V AC, full load. Typical	0,53
Power Factor at 230 V AC, full load. Typical	0,53
Power Reduction Of 60 To 70 ° C	3 W/°C
Ripple. max	50 mV pp
Series	Silverline
Supply Frequency	50-60 ±6 %
Szélesség	65 mm
Temperature Range Without Derating From	-10 °C
Temperature Range Without Derating To	60 °C
Type Power Supply	AS-Interface
Tömeg	0,62 kg
Védőanyag	Alumínium