Vizsgálat

TIGHT V4 IP67

Mikrokapcsoló

83186001
831860 ÁTK., W2S




- Névleges áram 0.1 A-tól 10 A/250 V/AC-ig
- Min. névleges áram 1 mA/4 V dc
- Két lehetséges pozíció vezérlőkar beépítésre
- A vezérlőkar két különböző pozícióba szerelhető

TERMÉKLEÍRÁS


MŰSZAKI ADATOK

A visszatérő mozgás min. ereje	0,8 N
Csatlakozás	W2S
Érintkezés típusa	Váltókapcsoló
IP-osztály	IP67, IP69
Kapcsolópont	8,4±0,3 mm
Max. hiszterézis	0,15 mm
Max. készenlét	9,3 mm
Max. működési erő	2,5 N
Max. üzemi hőmérséklet	125 °C
Max. üzemi összteljesítmény	4,2 N
Megengedett max. túlfeszültség	10 N
Min. túlszabályozás	0,6 mm
Min. üzemi hőmérséklet	-40 °C
Névleges áramerősség, 250 V AC	6 A
Nyitási távolság	0,4 mm
Termikus áramerősség, 250 V AC	7,5 A
Várható mechanikai élettartam	2x10^6 művelet (terhelés nélkül)


170 E
Arm with roll




170 A
Straight-arm




170 F
Arm with simulated scroll



W2S
Solder





Symmetric version
type 83 180/181/183/186




1 OL = 7.6 max.

Mounting bracket






Asymmetric version
typ 83 180/181/183/186



Attached with 2 M2 screws
Torque with screw only:
0.2 Nm, with screw + washer: 0.3 Nm

Cable Outputs




1 FG0
2 FD0
3 Standard 500 mm

Black = Common
Gray = NC
Blue = NO

Cross section:
83181 / 83 183 / 83 186 = 0.5 mm²
83 180 = 0.75 mm²


Cable outlet
B0 cable outlet on the bottom




1 Standard 500 mm

Black= Common
Gray = NC
Blue= NO

Cross section:
83181 / 83 183 / 83 186 = 0.5 mm²
83 180 = 0.75 mm²



Cable Outputs




1 CG0
2 CD0
3 Standard 500 mm


Black = Common
Gray = NC
Blue = NO

Cross section:
83181 / 83 183 / 83 186 = 3 x 0.5 mm²


Symmetric version
type 83 180/181/183/186




1 OL = 7.6 max.




170 E
Arm with roll




170 A
Straight-arm



170 F
Arm with simulated scroll




Symmetric version
type 83 180/181/183/186




1 OL = 7.6 max.


Mounting bracket




W2S
Solder




W7S
Flat plug



X1A
Straight circuit board connection




Asymmetric version
typ 83 180/181/183/186



Attached with 2 M2 screws
Torque with screw only:
0.2 Nm, with screw + washer: 0.3 Nm

Cable Outputs




1 FG0
2 FD0
3 Standard 500 mm

Black = Common
Gray = NC
Blue = NO

Cross section:
83181 / 83 183 / 83 186 = 0.5 mm²
83 180 = 0.75 mm²

Cable outlet
B0 cable outlet on the bottom




1 Standard 500 mm


Black= Common
Gray = NC
Blue= NO

Cross section:
83181 / 83 183 / 83 186 = 0.5 mm²
83 180 = 0.75 mm²


X1S
Straight PCB output




X2A - X2S
Side output, PCB rear



X3A - X3S
Side output, PCB front



Cable Outputs




1 CG0
2 CD0
3 Standard 500 mm

Black = Common
Gray = NC
Blue = NO


Cross section:
83181 / 83 183 / 83 186 = 3 x 0.5 mm²

Symmetric version
type 83 180/181/183/186




1 OL = 7.6 max.

W2S
Solderable



W7S
Connector 2.8 x 0.5



X1A
Circuit board

