



BANJO CSATLAKOZÁS, MŰANYAG

55 000 Sorozat

55500 6-M6

Egyfuratos üreges csavar, M6. Fekete




- PA test
- Acetálplaszt gyűrű
- Nyomás tartomány 20 bar-ig
- Nyomás tartomány 20 bar-ig
- Hőmérséklet tartomány -20 és + 80 ° C között



TERMÉKLEÍRÁS

MŰSZAKI ADATOK

Kiszerezelés	10 pc
Kivitel	B
Test anyaga	Nikkelezett sárgaréz



	A	B	L	CH	D
55500 4-M5	M5	14,0	19,5	9	10
55500 4-M6	M6	14,0	19,5	9	10
55500 4-1/8	1/8	16,5	21,5	14	10
55500 6-M5	M5	14,0	21,0	9	12
55500 6-M6	M6	14,0	21,0	9	12
55500 6-1/8	1/8	16,5	23,0	14	12
55500 6-1/4	1/4	18,5	25,5	18	12
55500 8-1/8	1/8	16,5	23,5	14	14
55500 8-1/4	1/4	18,5	26,0	18	14
55500 8-3/8	3/8	22,0	27,5	21	14
55500 10-3/8	3/8	22,0	30,5	21	17
55500 12-3/8	3/8	22,0	32,5	21	20
55500 12-1/2	1/2	26,0	35,0	26	20