



GHU9 INKREMENTÁLIS ÉRZÉKELŐ

GHU9-INKREMENTTIANTURI

- Felbontás max. 10 000 P / K
- IP 65, opcionálisan IP67
- 2 m kábellel vagy csatlakozóval
- Opcionális hajtómű



TERMÉKLEÍRÁS

MŰSZAKI ADATOK

Befoglalási átmérő	90 mm
Csatlakozás	Kábel, M23 érintkező
Érzékelő típusa	Differenciális
IP-osztály	IP66, IP67
Kilépés	Push/Pull
Max. impulzusszám	10000
Max. sebesség	6000 rpm
Max. tápfeszültség, DC	30 V DC
Max. üzemi hőmérséklet	100 °C
Min. tápfeszültség, DC	5 V DC
Min. üzemi hőmérséklet	-40 °C
Tengelyátmérő	30 mm

ORDERING REFERENCE (Contact the factory for special versions ex: overmold switch, electronics, special forges, connectors...)

GRU7	Short Ø	Available electronic	Output signal	Resolution	Connection	Connection orientation
GRU7 Cover: zinc Body: du	30: 30mm	2G2, 5G2, 5G5, 5GT, 5GH, 3G3	Y: A.A./B./O./P N: A.A. (pilot)	G4: M23 12 pins CW	G6: M23 12 pins CCW	8: radial
GRU7 Cover: zinc Body: stainless steel	32: 32mm	5: 11 to 30Vdc 3: 15 to 30Vdc	G2: driver 5Vdc 85402 G3: driver 12Vdc G5: 11 to 30Vdc G7: push-out G8: push-out 11-30Vdc G9: push-out 11-30Vdc 130 mA	10 000 max N: A.A./B./O./P (unpiloted) G3: PVC cable 8 wires G20: usual 2m cable GP: PUR cable 12 wires		
Ex: GRU7	30 // 5	G5	Y // 5 000 //	GP		8050

Available resolutions: 1 2 3 4 5 6 7 8 9 10 12 13 14 15 16 19 20 21 24 25 26 28 29 30 32 33 36 39 40 43 45 46 48 50 54 56 58 60 63 64 66 67 70 72 74 75 76 80 84 86 88 89 90 91 94 96 100 101 110 120 122 123 125 127 129 130 132 133 135 140 147 150 157 159 160 168 169 170 172 173 180 186 191 196 200 201 205 220 222 225 234 240 241 242 243 246 248 250 254 255 256 258 259 262 264 272 283 285 290 300 305 314 315 318 320 330 340 350 360 365 367 375 378 380 381 386 390 395 400 405 410 424 425 438 443 450 471 480 489 495 500 510 512 513 524 540 550 565 580 600 623 625 628 630 632 633 635 660 680 700 720 746 750 752 754 804 800 810 840 860 880 891 900 940 960 1000 1024 1080 1100 1131 1200 1223 1250 1260 1280 1290 1400 1414 1440 1500 1536 1570 1600 1620 1630 1700 1800 1885 2000 2048 2250 2400 2500 2640 3000 3456 3600 3680 3750 4000 4096 4300 4900 5000 7200 9000 10000

