



HCW4 - NEM ÉRINTKEZŐ INKREMENTÁLIS ÉRZÉKELŐ

HCW4PG590032G3

- Felbontás max. 1024 P / K
- A, B és Z csatornák és ugyanaz invertálva
- IP67, opcionális IP69K
- 2m kábellel



TERMÉKLEÍRÁS

MŰSZAKI ADATOK

Befoglalási átmérő	50 mm
Csatlakozás	Kábel
Érzékelő típusa	Differenciális
Felbontás	32 P/R
IP-osztály	IP67
Kilépés	Push/Pull
Max. tápfeszültség, DC	30 V DC
Max. üzemi hőmérséklet	85 °C
Min. tápfeszültség, DC	5 V DC
Min. üzemi hőmérséklet	-40 °C

STANDARD CONNECTION

		-	+	A	B	0	A/	B/	Q/	Ground
G3	PVC cable 3 wires 620/450	WH white	BN brown	GN green	YE yellow	GY grey	PK pink	BU blue	RD red	Main shield
GP	PUR cable 12 wires 620/450	WH:white + WH/GN white/green	BU:blue + BN/GN brown/green	GY grey	BN brown	RD red	PK pink	GN green	BK black	General shielding

ORDERING REFERENCE (Contact the factory for special versions, ex: stainless steel version, connections...)

	Mechanics	Supply Output stage	Signals	Resolution	Connection	Connection description
HCW4	00	5V2 Modulator SVC TL / KS42 output	A, // B, // 0, G2	1024 max	G3 : PVC cable 8 wires	R001 Rigid cable 2m
		PG5 5 to 30Vdc Push-pull output TL / KS42 enables if encoder supply is 5Vdc2			GF: PWR cable 12 wires	
Ex: HCW4	00 //	PG5	9 //	01024 //	G3	R020

AVAILABLE RESOLUTIONS

32 64 128 256 1024

