



HCW4 - NEM ÉRINTKEZŐ INKREMENTÁLIS ÉRZÉKELŐ

HCW4PG590128G3

- Felbontás max. 1024 P / K
- A, B és Z csatornák és ugyanaz invertálva
- IP67, opcionális IP69K
- 2m kábellel



TERMÉKLEÍRÁS

MŰSZAKI ADATOK

Befoglalási átmérő	50 mm
Csatlakozás	Kábel
Érzékelő típusa	Differenciális
Felbontás	128 P/R
IP-osztály	IP67
Kilépés	Push/Pull
Max. tápfeszültség, DC	30 V DC
Max. üzemi hőmérséklet	85 °C
Min. tápfeszültség, DC	5 V DC
Min. üzemi hőmérséklet	-40 °C

STANDARD CONNECTION

		-	+	A	B	0	A/	B/	G/	Ground
G3	PVC cable 3 wires 6200/600	WH white	BN brown	GN green	YE yellow	GY grey	PK pink	BU blue	RD red	Main shield
G4	PUR cable 12 wires 6200/450	WH white + WH/GN white/green	BU blue + BN/GN brown/green	GY grey	BN brown	RD red	PK pink	GN green	BK black	General shielding

ORDERING REFERENCE (Contact the factory for special versions, ex: stainless steel version, connections,...)

	Mechanics	Supply Output stage	Signals	Resolution	Connection	Connection description
HC94	00	5V2 Modulator TL / RS422 output	A, / B, / 0, /2	1024 max	G3 : PVC cable 8 wires	R001 Rigid cable 2m
Incremental encoder		PG5 5 to 30Vdc Push-pull output TL / RS422 enables if encoder supply is 5Vdc2			GF: PWR cable 12 wires	
Ex: HC94	00 //	PG5	9 //	01024 //	G3	R020

AVAILABLE RESOLUTIONS

32 64 128 256 1024

