



TCW4 - NEM ÉRINTKEZŐ SSI ABSZOLÚT KÓDOLO

TCW4-SSI

- 12 bit a felbontáshoz és 16 bites a fordulathoz
- Robusztus konstrukció nagy rezgés- és ütésállósággal
- IP67, opcionális IP69K



TERMÉKLEÍRÁS

MŰSZAKI ADATOK

Befoglalási átmérő	52 mm
Csatlakozás	Kábel
Érzékelő típusa	Abszolút
Felbontás	Max. 12 bit resoluitiolla ja 16 bit kierroksille
IP-osztály	IP67
Kilépés	SSI
Max. tápfeszültség, DC	30 V DC
Max. üzemi hőmérséklet	85 °C
Min. tápfeszültség, DC	5 V DC
Min. üzemi hőmérséklet	-40 °C
Verzió	Többmenetes

STANDARD SSI CONNECTION									
Ref.	Type	+Vcc	0 V	Ck+	Data+	RAZ	Data-	Ck-	Direction
SS	SSI cable PUR (S330500)	Br/GN	Wh/GN	GN	GY	BU	PE	Br	Wh
		Brown/Green	White/Green	Green	Gray	Blue	Pink	Brown	White
									General shielding

DIRECTION input		RAZ / RAZ input	
Level '0' 0 V Level '1' 0.7VxVcc Effective -Red	Level '0' 0 V Level '1' 6 V Effective -Red	Notes: Do not connect other grounds, connect DIRECTION and RAZ to a potential (RAZ or 0V if not used)	

TCW4 ORDERING REFERENCE (Contact the factory for special versions, ex. dimensions, connections...)									
TCW4 :	Mechanics	Supply	Output stage	Code	Resolution	Connection	Orientation		
	00 : Magnetic Absolute multi-turn encoder	P : 5 to 30Vdc	SS : SSI without parity	B : Binary G : Gray	128/1306 : 25 bits 128/1204 : 24 bits	SS : PUR cable 50cm radial cable	R005 :		
Ex: TCW4.	00 //	P	SS	G //	128/1305 //	SS	R005		

